

Ingegoten transformatoren geschikt voor DIN-rail montage



- Dubbel geïsoleerd
- Snelle montage
- Uit voorraad leverbaar
- Andere uitvoeringen mogelijk

U pri	230 VAC									
U sec (AC)	2x12 V	24 V	24 V							
Usec 2 (DC)			24 V							
T ambient				Afmetingen						afzekeren
				zonder klem			inclusief klem			
VA	Type No.			B	D	H	B	D	H	met (A-T):
20	N230-24 DIN			52	58	85				x
30		ST-557.89A		72	70	73	72	96	73,0	1,25AT
50		ST-557.90A		72	70	73	72	96	73,0	2,0AT
70		ST-557.91A		84	76	82	84	105	82,0	3,15AT
100		ST-574.13A		84	76	82	84	105	82,0	4,0AT
24			ST-573.93A	84	76	82	84	105	82,0	1,0AT/1,0AT



Belpa B.V.
Postbus 800 - 3840 AV Harderwijk
Nobelstraat 48 - 3846 CG Harderwijk
Telefoon : +31 (0) 341 46 20 20
Telefax : +31 (0) 341 42 52 67
E-mail : info@belpa.nl
Internet : www.belpa.nl

ING Bank rek.nr. 67.16.96.858
IBANnr NL88ingB0671696858
SWIFT INGBNL2A
Postbank 831237
Handelsreg.nr. 08016318 KvK Harderwijk
BTWnr. NL005216709B03