

1 FASE VOEDINGSTRANSFORMATOREN

VOLGENS EN 61558-2.6



Typenummer	Omschrijving	Afmeting	Gewicht
TR-156.19.2	Veiligheidstransformator 230/400V-24V-25VA	66x53x95	0,80
TR-156.20.2	Veiligheidstransformator 230/400V-24V-63VA	78x80x91	1,30
TR-156.21.2	Veiligheidstransformator 230/400V-24V-100VA	84x97x95	2,00
TR-156.22.2	Veiligheidstransformator 230/400V-24V-160VA	96x97x106	2,80
TR-156.23.2	Veiligheidstransformator 230/400V-24V-250VA	120x96x138	4,00
TR-156.24.2	Veiligheidstransformator 230/400V-24V-400VA	120x141x135	6,70
TR-156.25.2	Veiligheidstransformator 230/400V-24V-630VA	150x122x156	8,30
TR-172.63	Veiligheidstransformator 230V-24V-25VA	66x67x78	0,70
TR-172.63Z	Veiligheidstransformator 230V-24V-25VA +1 zek.	66x67x78	0,66
TR-172.63ZZ	Veiligheidstransformator 230V-24V-25VA +2 zek	66x67x78	0,66
TR-172.65	Veiligheidstransformator 230V-24V-63VA	78x71x87	1,20
TR-172.65Z	Veiligheidstransformator 230V-24V-63VA +1 zek.	78x71x87	1,20
TR-172.65ZZ	Veiligheidstransformator 230V-24V-63VA +2 zek.	78x71x87	1,20
TR-172.66	Veiligheidstransformator 230V-24V-100VA	84x88x92	2,10
TR-172.66Z	Veiligheidstransformator 230V-24V-100VA +1 zek.	84x88x92	2,10
TR-172.66ZZ	Veiligheidstransformator 230V-24V-100VA +2 zek.	84x88x92	2,10
TR-172.67	Veiligheidstransformator 230V-24V-160VA	96x90x103	2,90
TR-172.67Z	Veiligheidstransformator 230V-24V-160VA +1 zek.	96x90x103	2,90
TR-172.67ZZ	Veiligheidstransformator 230V-24V-160VA +2 zek.	96x90x103	2,90
TR-172.68	Veiligheidstransformator 230V-24V-250VA	96x106x103	3,70
TR-172.68Z	Veiligheidstransformator 230V-24V-250VA +1 zek.	96x106x103	3,70
TR-172.68ZZ	Veiligheidstransformator 230V-24V-250VA +2 zek.	96x106x103	3,70



Belpa B.V.
 Postbus 800 - 3840 AV Harderwijk
 Nobelstraat 48 - 3846 CG Harderwijk
 Telefoon : +31 (0) 341 46 20 20
 Telefax : +31 (0) 341 42 52 67
 E-mail: info@belpa.nl
 Internet: www.belpa.nl

ING Bank rek.nr. 67.16.96.858
 IBANnr NL88ingB0671696858
 SWIFT INGBNL2A
 Postbank 831237
 Handelsreg.nr. 08016318 KvK Harderwijk
 BTWnr. NL005216709B03